



## HGS (INDIA) LIMITED



### HG-5 LF Geophone Element





Based on the technology transfer for manufacturing the SM® range of geophones from Sensor® Nederland BV, HGS (India) Limited (erstwhile Geosource India Limited) offers the HG-5 LF geophone with 2 Hz natural frequency for picking up low frequency and deep level signals. The low frequency response is attained by the addition of a resistor - capacitor (RC) network.

Applications: Vibration monitoring & Seismology

- Features:
- Low frequency geophone with the smallest form factor in the industry
  - Very low frequency
  - High Sensitivity
  - Distortion  $\leq 0.9\%$
  - Rugged design with rotating-coil contacts

### Specifications - HG-5 LF 2 Hz 9800 Ohm

	<b>Implicit parameters</b>	<b>Explicit parameters</b>	
	<b>Value</b>	<b>Value</b>	
Natural frequency	2 Hz	4.5 Hz	
Tolerance	± 20%	± 0.5 Hz	
Distortion	≤0.9%	≤0.1%	
Damping	0.7	0.65	
Tolerance	± 20%	± 5%	
Sensitivity	34 V/m/s	204 V/m/s	
Tolerance	± 20%	± 5%	
Moving mass	2.7 g	13.5 g	
Max coil excursion p.p .	3 mm	3 mm	
Coil Resistance	9800 Ω	11500 Ω	
Tolerance	± 10%	± 5%	
<b>Physical Characteristics</b>			
Diameter	26.7 mm	26.7 mm	
Height	44 mm	39.3 mm	
Weight	105 g		
Operating temperature range	-40°C to 70°C		
<b>Warranty Period*</b>	1 year		
*Warranty excludes damage caused by high voltage and physical damage to the element case.			
All parameters are specified at +20°C in the working position unless stated otherwise.			

Version 1.0

Description	Part No.	Working position
HG-5 LF U 2 Hz 9800 Ohm	SG000554	Upright
HG-5 LF H 2 Hz 9800 Ohm	SG000555	Horizontal

<b>India</b> HGS (India) Ltd Tel : +91-11-46066604 Website : www.hgsindia.com	<b>The Netherlands</b> HGS Products B.V. Tel : +31 708200820 Website : www.hgsproducts.nl
----------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------