



Applications

- High temperature environment
- Industrial applications
- Critical turbo machinery
- Bearing vibration monitoring
- Hydro, electric and wind turbines

Features


- Rugged design with rotating-coil contacts
- Orientation vertical to horizontal
- High temperature

Specifications


Frequency [Hz]	14 ±5%	Maximum tilt angle [°]	90
O.C. Damping	0.233 ±5%		
O.C. Sensitivity [V/m/s]	42.8 ±5%		
Resistance [Ω]	900 ±5%	Dimensions [mm]	∅25.4 x 36
Moving mass [g]	10.5	Weight [g]	90
Max coil excursion p.p. [mm]	4	Operating temperature [°C]	-40 to 200
Shunt for 0.7 damping [Ω]	1200	Warranty ¹	3 months
Distortion with 17.78 mm/s p.p. coil-to-case velocity at 14 Hz			≤ 0.5%

All parameters are specified at +20°C in the working position unless stated otherwise
¹ Warranty excludes damage caused by high voltage and physical damage to the element case

Response



Phase




Ordering information

Part	Description	Working position	Polarity
SG000199	HG-6 YB 14 Hz 900 ohm HT	Vertical to horizontal	Tap on the pins gives positive signal

Contact

India
 HGS (India) Ltd
 Tel : +91-11-46066604
www.hgsindia.com



The Netherlands
 HGS Products B.V.
 Tel : +31 708200820
www.hgsproducts.nl

